



DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H
-	-	-	-	23	-	-

MODEL

MODEL: TS -	PANEL COLOR
PANEL MATERIAL	<input type="checkbox"/> BLUE
<input type="checkbox"/> 2-PLY RILON	<input type="checkbox"/> ORANGE
<input type="checkbox"/> 3-PLY RILON	<input type="checkbox"/> OTHER
<input type="checkbox"/> OTHER	

ELECTRICAL OPTIONS

- 460v - 3ph
- 230v/208v - 3ph
- 230v/208v - 1ph
- 575v - 3ph
- OTHER

STANDARD FEATURES

1. WIRELESS BOTTOM BAR (NO COIL CORD)
2. (1) FACTORY INSTALLED SIDE COLUMN PHOTOEYE
3. (1) FIELD INSTALLED PHOTOEYE
4. FRONT HEAT LAMPS MOUNTED INDEPENDENTLY ON WALL
5. HEAT TAPE IN SIDE COLUMNS & ACROSS SPREADER
6. ROTARY DISCONNECT ON CONTROL BOX FOR TEC LIGHTS
7. SYSTEM 4 AC DRIVE
8. LH MOTOR ASSEMBLY
9. 208V & 230V REQUIRE 50 AMP SERVICE
460V & 575V REQUIRE 30 AMP SERVICE
10. HOOD NOT RECOMMENDED
11. WINDOWS NOT RECOMMENDED

STANDARD OPTIONS

- SLANT HOOD FLAT HOOD
- 17" WINDOWS: ONE TWO THREE
- WINDRIBS: ONE TWO THREE
- THRU WALL BRAKE RELEASE
- 575/460V STEP DOWN TRANSFORMER INCLUDED IN RYTEC CONTROL BOX
- ROTARY DISCONNECT (NOT FUSED)
- OTHERS (DESCRIBE IN NOTES)

ACTIVATION

- PHOTOEYE
- PULL CORDS
- MOTION DETECTOR
- RADIO CONTROL
- PUSHBUTTON
- FLOOR LOOP
- OTHERS (DESCRIBE IN NOTES)

OPTION NOTES

NOTES:

RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING

TURBO SEAL® w/ TEC LIGHTS-SYSTEM 4

APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

CUSTOMER: _____

LOCATION: _____

DATE: 11/30/11

DRAWING NO.: 401054-00T REV.: -

NOTES:
RYTEC CORP. DOES NOT GUARANTEE A FROST FREE DOOR. THE RANGE OF THE TEC LIGHTS IS APPROXIMATELY TEN (10) VERTICAL FEET. DEPENDING ON SITE CONDITIONS AND RELATIVE HUMIDITY, IT IS POSSIBLE FOR FROST TO BUILD UP ON THE LOWER PORTION OF THE DOOR PANEL.